

What is claimed is:

1. A method of checking for errors in line width in an integrated circuit, comprising:

identifying with a marker any lines having a line width greater than a default minimum line width;

associating a line width parameter with each line width marker, the line width parameter corresponding to a line width for the marked line;

converting the line width parameters and line width markers to lines in a layout;

and

comparing the line width parameter for each line width marker with an actual layout line width.
2. The method of claim 1, and further comprising containing each line width marker in a line width layer of the layout.
3. The method of claim 1, wherein the layout further comprises a component layer having components of the integrated circuit.
4. The method of claim 1, and further comprising indicating an error when the actual layout line width is less than the line width parameter.
5. The method of claim 1, and further comprising recording an error when the actual layout line width is less than the line width parameter.
6. The method of claim 1, and further comprising excluding checking for errors in areas of the integrated circuit near or above a connected transistor.

7. The method of claim 1, wherein the lines having a line width greater than a default minimum line width comprise lines for carrying power to transistors of the integrated circuit.
8. A method of checking for errors in line width in an integrated circuit, comprising:
 - defining a line width layer;
 - identifying with a marker any lines having a line width greater than a default minimum line width;
 - associating a line width parameter with each line width marker, the line width parameter corresponding to a line width for the marked line;
 - converting the line width parameters and line width markers to lines in a layout;
 - and
 - comparing the line width parameter for each line width marker with an actual layout line width.
9. The method of claim 8, and further comprising indicating an error when the actual layout line width is less than the line width parameter.
10. The method of claim 8, and further comprising recording an error when the actual layout line width is less than the line width parameter.
11. The method of claim 8, wherein the line width layer contains each line width marker.
12. The method of claim 8, and further comprising excluding checking for errors in areas of the integrated circuit near or above a connected transistor.

13. The method of claim 8, wherein the lines having a line width greater than a default minimum line width comprise lines for carrying power to transistors of the integrated circuit.
14. A method of checking for errors in line width in an integrated circuit, comprising:
 - identifying with a marker any lines having a line width greater than a default minimum line width;
 - containing each line width marker in a line width layer;
 - associating a line width parameter with each line width marker, the line width parameter corresponding to a line width for the marked line;
 - converting the line width parameters and line width markers to lines in a layout;
 - comparing the line width parameter for each line width marker with an actual layout line width; and
 - generating an error condition when the actual layout line width is less than the line width parameter.
15. The method of claim 14, wherein the layout further comprises a component layer having components of the integrated circuit.
16. The method of claim 14, wherein the lines having a line width greater than a default minimum line width comprise lines for carrying power to transistors of the integrated circuit.
17. The method of claim 14, and further comprising indicating or recording the error condition.

18. A method of checking for errors in line width in an integrated circuit, comprising:
- identifying with a marker any lines having a line width greater than a default minimum line width;
 - containing each line width marker in a line width layer;
 - associating a line width parameter with each line width marker, the line width parameter corresponding to a line width for the marked line;
 - converting the line width parameters and line width markers to lines in a layout;
 - comparing the line width parameter for each line width marker with an actual layout line width;
 - indicating or recording an error when the actual layout line width is less than the line width parameter; and
 - excluding checking for errors in areas of the integrated circuit near or above a connected transistor.
19. The method of claim 18, wherein the layout further comprises a component layer having components of the integrated circuit.
20. The method of claim 18, wherein the lines having a line width greater than a default minimum line width comprise lines for carrying power to transistors of the integrated circuit.